

# TEST CASE DOCUMENTATION AND TESTING RESULTS

ANSYS-QA-LS-DYNA-AWG-CI-6-10

TEST CASE ID AWG-CI-6

Tension Member - Aft Seat Leg, Tension  
Bar

Tested with LS-DYNA® R14.1 Revision 7-gea5f83301c

Monday 24<sup>th</sup> April, 2023



**Warranty Disclaimer:**

The test case(s) described herein are for illustrative purposes only. ANSYS does not warrant that a user of these or other LS-DYNA features will experience the same or similar results or that a feature will meet the user's particular requirements or operate error free. FURTHERMORE, THERE ARE NO WARRANTIES, EITHER EXPRESS OR IMPLIED, ORAL OR WRITTEN, WITH RESPECT TO THE DOCUMENTATION AND SOFTWARE DESCRIBED HEREIN INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTIES (i) OF MERCHANTABILITY, OR (ii) FITNESS FOR A PARTICULAR PURPOSES, OR (iii) ARISING FROM COURSE OF PERFORMANCE OR DEALING, OR FROM USAGE OF TRADE OR. THE REMEDIES SET FORTH HEREIN ARE EXCLUSIVE AND IN LIEU OF ALL OTHER REMEDIES FOR BREACH OF WARRANTY.

| Document Information |                                                      |
|----------------------|------------------------------------------------------|
| Confidentiality      | <b>external use</b>                                  |
| Document Identifier  | ANSYS-QA-LS-DYNA-AWG-CI-6-10                         |
| Author(s)            | Prepared by LS-DYNA® Aerospace Working Group         |
| Number of pages      | 14                                                   |
| Date created         | Monday 24 <sup>th</sup> April, 2023                  |
| Distribution         | LS-DYNA® Aerospace Working Group / internal ANSYS QA |

# Contents

|          |                                                   |           |
|----------|---------------------------------------------------|-----------|
| <b>1</b> | <b>Introduction</b>                               | <b>1</b>  |
| 1.1      | Purpose of this Document . . . . .                | 1         |
| <b>2</b> | <b>Test Case Information</b>                      | <b>2</b>  |
| <b>3</b> | <b>Test Case Specification</b>                    | <b>3</b>  |
| 3.1      | Test Case Purpose . . . . .                       | 3         |
| 3.2      | Test Case Description . . . . .                   | 4         |
| 3.3      | Model Description . . . . .                       | 5         |
| <b>4</b> | <b>Test Specifications</b>                        | <b>6</b>  |
| 4.1      | Test Case Targets . . . . .                       | 6         |
| 4.2      | Pass/Fail Criteria . . . . .                      | 7         |
| <b>5</b> | <b>Test Case Results</b>                          | <b>8</b>  |
| 5.1      | Software and Hardware Specifications . . . . .    | 8         |
| 5.2      | Results Summary . . . . .                         | 9         |
| 5.3      | Result Details . . . . .                          | 10        |
| 5.3.1    | Test Target 1: X-component Displacement . . . . . | 11        |
| 5.3.2    | Test Target 2: Internal Energy . . . . .          | 12        |
| 5.3.3    | Test Target 3: CPU time . . . . .                 | 13        |
|          | <b>References</b>                                 | <b>14</b> |

# **1 Introduction**

## **1.1 Purpose of this Document**

This document specifies the test case AWG-CI-6. It provides general test case information like name and ID as well as information to the confidentiality, status, and classification of the test case.

A detailed description of the test case is given, the purpose of the test case is defined, and the tested features are named. The test case specifications also state the target measures for testing and the expected results, as well as their pass and fail criteria.

Testing results are provided in section 5 for the therein mentioned LS-DYNA® version and platforms.

## 2 Test Case Information

| Test Case Summary        |                                            |
|--------------------------|--------------------------------------------|
| Confidentiality          | external use                               |
| Test Case Name           | Tension Member - Aft Seat Leg, Tension Bar |
| Test Case ID             | AWG-CI-6                                   |
| Test Case Status         | active                                     |
| Test Case Classification | Application Benchmark                      |
| Test Case Source         | Boeing                                     |
| Tested Keyword           | *ELEMENT_SOLID *MAT_ELASTC                 |
| Member of Test Suite     | AWG CI SUITE                               |
| Metadata                 | AWG CI                                     |

Table 1: Test Case Summary

### **3 Test Case Specification**

#### **3.1 Test Case Purpose**

The purpose of Test Case ID AWG-CI-6 is to simulate a tensile load on a rod that is representative of an aft seat leg, tension member or a portion of an actuator that is subjected to tensile, compressive, and compression, bending loads.

### 3.2 Test Case Description

A pull test scenario is simulated with 0.15 GPa of pressure applied to the free end of a rod that has the other end fixed in all degrees of freedom as shown in Figure 1.




Figure 1: Tension member.



3.3 Model Description

An aluminum (2024-T351) rod with a 228.6 mm (9 inch) length and 12.7 mm (0.5 inch) diameter is fixed at one end in all degrees of freedom as shown in Figure 1. The other end of the rod has a 0.15 GPa pressure applied. Displacement of a node on the free end is monitored along with the internal energy of the rod. The Finite Element Model is shown in Figure 2.




Figure 2: Rod Finite Element Model

| Model information |                                                             |
|-------------------|-------------------------------------------------------------|
| Nodes             | 1593                                                        |
| Solid elements    | 1160                                                        |
| Materials         | 1                                                           |
| Parts             | 1                                                           |
| Units             | mm (length), ms (time), kg (mass), kN (force,) GPa (stress) |

Table 2: FEA Model Information

| Model information |                              |
|-------------------|------------------------------|
| Test Case ID      | Input Deck Name              |
| 1                 | tension_bar_aft_seat_leg.key |

Table 3: Specification of sub test cases

## 4 Test Specifications

### 4.1 Test Case Targets

| Test Case Targets |                          |                |              |                    |
|-------------------|--------------------------|----------------|--------------|--------------------|
| Target number     | output                   | component type | component id | retrieved from     |
| 1                 | X-component Displacement | Node           | 1301         | binout/nodout file |
| 2                 | Internal Energy          | Part           | 1            | binout/glstat file |
| 3                 | CPU Time                 |                |              | d3hsp file         |

Table 4: Test Case targets for Test Case ID AWG-CI-6

## 4.2 Pass/Fail Criteria

These are the Pass/Fail criteria used for the Validation of the Test Case ID AWG-CI-6.

The sub test case passes if the test case target data falls within the corridor bounds. Otherwise the test fails.

The test case corridors are upper and lower bounds for the test case targets. They were defined based on the test target data obtained with LS-DYNA® R14.0 Revision 114 binaries by the following process:

- For a specific test case target, interpolate the data from different platform and executable (R14.0 Revision 114) combinations, so that the time domain is the same.
- Calculate the upper and lower bounds by:

$$bound_{up}(i) = max(i) + 0.2 \times [max(i) - min(i)] + 0.05 \times peak$$

$$bound_{low}(i) = min(i) - 0.2 \times [max(i) - min(i)] - 0.05 \times peak$$

where  $max(i)$ ,  $min(i)$  are the maximum and minimum values at the  $i_{th}$  time step across all platforms and executable (R14.0 Revision 114) combinations the test case was calculated with,  $peak$  is the maximum absolute y value across the whole time domain,  $bound_{up}(i)$  and  $bound_{low}(i)$  are the upper and lower bounds for the  $i_{th}$  time step.

For CPU Time target, it holds:

$$bound_{up}^{CPU\ Time} = 2 \times Max + 1$$

$$bound_{low}^{CPU\ Time} = 0$$

where  $Max$  is the maximum CPU Time (in seconds) across all platforms and executable (R14.0 Revision 114) combinations the test case was calculated with and  $bound_{up}^{CPU\ Time}$  and  $bound_{low}^{CPU\ Time}$  are the upper and lower bounds.

## 5 Test Case Results

### 5.1 Software and Hardware Specifications

In order to ensure cross-platform consistency, the herein mentioned sub test cases are run on platforms specified in table 5 and the results are calculated with software versions defined in table 6.

| Platform Name | Operating system | CPU type                              | MPI-Protocol                                              | Number of cpu's <sup>1</sup> |
|---------------|------------------|---------------------------------------|-----------------------------------------------------------|------------------------------|
| cdcvdce7mbu01 | CentOS 7.9       | Intel® Xeon®<br>E5- 2680 v4 @ 2.40GHz | Platform MPI ISV Edition<br>08.3.0.2 [10692] Linux x86-64 | 4                            |

<sup>1</sup> Number of cpu's used for calculation of the test case

Table 5: Used Platforms and CPU Type's

| Product  | Version | Release | Revision      | Parallel type <sup>1</sup> | Precision <sup>2</sup> | executable                 |
|----------|---------|---------|---------------|----------------------------|------------------------|----------------------------|
| LS-DYNA® | 971     | R14.1   | 7-gea5f83301c | SMP                        | SP                     | ls971.7-gea5f83301c.R14.1  |
| LS-DYNA® | 971     | R14.1   | 7-gea5f83301c | SMP                        | DP                     | ld971.7-gea5f83301c.R14.1  |
| LS-DYNA® | 971     | R14.1   | 7-gea5f83301c | MPP                        | SP                     | mpp971.7-gea5f83301c.R14.1 |
| LS-DYNA® | 971     | R14.1   | 7-gea5f83301c | MPP                        | DP                     | mpd971.7-gea5f83301c.R14.1 |

<sup>1</sup> MPP = Massively Parallel Processing, SMP = Symmetric Multiprocessing

<sup>2</sup> SP = single precision, DP = double precision

Table 6: Tested LS-DYNA® version

## 5.2 Results Summary

Table 7 contains the results of the Test Case ID AWG-CI-6 completed with all combinations of software and hardware defined in section 5.1 (1 \* 1 \* 4 total calculation runs).

Details on the test results can be found in the section 5.3.

The table 7 cross cpu architecture consistency summary is:

- **PASS** - Pass criteria in section 4.2 is attained.
- **FAILED** - Pass criteria in section 4.2 is not attained.
- **ERROR** - sub test case terminates due to error.
- **N/A** - sub test case was not calculated.

| Sub Test Case ID | PASS/FAILED |
|------------------|-------------|
| 1                | <b>PASS</b> |

Table 7: Results summary for Test Case ID AWG-CI-6

### 5.3 Result Details

The following subsections contain detailed results for the Test Case ID AWG-CI-6 for LS-DYNA® R14.1 Revision 7-gea5f83301c.

For each sub test case defined in section 3.3 there is a graph displaying the time history of the result target defined in section 4.1 for the platform and software version combinations defined in section 5.1.

The title of the graph states the test case ID and the name of input deck. The legend contains the type, branch and the revision of the executable.

5.3.1 Test Target 1: X-component Displacement




Figure 3: X-component Displacement of Node 1301.

### 5.3.2 Test Target 2: Internal Energy




Figure 4: Internal Energy of Part 1.



### 5.3.3 Test Target 3: CPU time




Figure 5: CPU Time Comparison.

## References